

PROYECTORES ACÚSTICOS ESFÉRICOS

SPS-5121PW

12 W

100 dB

SPS-6301PW

30 W

106 dB

Proyectores acústicos colgantes de recinto esférico, para instalar suspendidos del techo y reducir la distancia del altavoz a las personas que deben recibir los avisos.



IP35

	SPS-5121PW	SPS-6301PW
Potencia RMS	12 W (15 W máx)	30 W (35 W máx)
Altavoz	5"	6,5"
Selección de potencia	12, 9, 6, 3 y 1 W	30, 20, 15, 10 y 5 W
Conexión a 8 ohm	disponible	disponible
Respuesta en frecuencia	150 ~ 20.000 Hz	100 ~ 20.000 Hz
SPL 1 m 1 kHz	89 dB (1 W) / 100 dB (12 W)	91 dB (1 W) / 106 dB (30 W)
Grado de protección	IP35 (IEC-529)	IP35 (IEC-529)
Dimensiones (mm)	180 (diámetro)	264 (diámetro)
Peso	1,4 kg	2,3 kg
Acabados	plástico ABS, color marfil	plástico ABS, color marfil

SPHERICAL ACOUSTIC PROJECTORS

SPS-5121PW

12 W

100 dB

SPS-6301PW

30 W

106 dB

Pendant acoustic projectors in a spherical surround for hanging on the ceiling and reducing the distance from the loudspeaker to the people who have to hear the announcements.



IP35

	SPS-5121PW	SPS-6301PW
RMS power	12 W (15 W max)	30 W (35 W max)
Loudspeaker	5"	6.5"
Power selection	12, 9, 6, 3 and 1 W	30, 20, 15, 10 and 5 W
Connection at 8 Ohm	available	available
Frequency response	150 ~ 20,000 Hz	100 ~ 20,000 Hz
SPL 1 m 1 kHz	89 dB (1 W)/100 dB (12 W)	91 dB (1 W)/106 dB (30 W)
Protection	IP35 (IEC-529)	IP35 (IEC-529)
Dimensions (mm)	180 (diameter)	264 (diameter)
Weight	1.4 Kg	2.3 Kg
Finishing	ABS ivory colour plastic	ABS ivory colour plastic