

RACKS DE MEGAFONÍA

ARMARIOS RACK (BASTIDORES DE 19")

AR-18K

Muebles para albergar los elementos de las centrales de megafonía, de anchura normalizada de 19", fondo de 800 mm y altura según las necesidades (18, 27, 37 y 42 unidades).

AR-27K

AR-37K

AR-42K

Incorporan ruedas, paneles laterales practicables, panel posterior con llave, ventiladores superiores y opcionalmente puerta frontal de cristal templado con llave.



Accesorios

| | |
|--------|---|
| Z-45 | Placa (2u) con interruptor general y magnetotérmico 20 A |
| Z-42 | Placa (3u) con interruptor general, altavoz monitor y control de volumen |
| Z-42S | Placa (3u) con interruptor general, altavoz monitor, selector de 6 canales y control de volumen |
| Z-46 | Placa (3u) con altavoz monitor y control de volumen |
| Z-46S | Placa (3u) con altavoz monitor, selector de 6 canales y control de volumen |
| Z-60 | Placa ciega (1 u = 44 mm) |
| Z-60PF | Placa ciega perforada (1 u = 44 mm) |
| Z-61 | Placa ciega (2 u = 89 mm) |
| Z-62 | Placa ciega (3 u = 133 mm) |
| Z-63 | Placa ciega (4 u = 176 mm) |

Consulte con OPTIMUS si desea el suministro del armario totalmente montado, cableado, verificado y con la documentación técnica específica de su instalación.

| | AR-18K | AR-27K | AR-37K | AR-42K |
|---------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
| Unidades de altura | 18 | 27 | 37 | 42 |
| Anchura interior | 488 mm (19") | 488 mm (19") | 488 mm (19") | 488 mm (19") |
| Dimensiones exteriores | | | | |
| Ancho (mm) | 600 | 600 | 600 | 600 |
| Fondo (mm) | 800 | 800 | 800 | 800 |
| Alto (mm) | 985 | 1385 | 1830 | 2055 |
| Ventilación | 4 ventiladores incorporadas | 4 ventiladores incorporadas | 4 ventiladores incorporadas | 4 ventiladores incorporadas |
| Ruedas | incorporadas | incorporadas | incorporadas | incorporadas |
| Puerta frontal (opcional) | PK-18 | PK-27 | PK-37 | PK-42 |



PUBLIC ADDRESS RACKS

RACK CABINETS (19" FRAMES)

- AR-18K** Furniture for housing the elements of the PA units with a standard width of 19", 800 mm in depth and height as needed (18, 27, 37 and 42 units).
- AR-27K**
- AR-37K** They incorporate wheels, practicable side panels, rear panel with key, top fans and optionally a tempered glass front door with key.
- AR-42K**



Accessories

| | |
|---------------|---|
| Z-45 | Plate (2u) with main switch and 20 A circuit breaker |
| Z-42 | Plate (3u) with main switch, monitor loudspeaker and volume control |
| Z-42S | Plate (3u) with main switch, monitor loudspeaker, 6-channel selector and volume control |
| Z-46 | Plate (3u) with monitor loudspeaker and volume control |
| Z-46S | Plate (3u) with monitor loudspeaker, 6-channel selector and volume control |
| Z-60 | Blind plate (1 u = 44 mm) |
| Z-60PF | Perforated blind plate (1 u = 44 mm) |
| Z-61 | Blind plate (2 u = 89 mm) |
| Z-62 | Blind plate (3 u = 133 mm) |
| Z-63 | Blind plate (4 u = 176 mm) |

Consult OPTIMUS if you want the cabinet supplied assembled, wired, checked and with the specific technical documentation of your installation.

| | AR-18K | AR-27K | AR-37K | AR-42K |
|-----------------------|---------------|---------------|---------------|---------------|
| Height units | 18 | 27 | 37 | 42 |
| Interior width | 488 mm (19") | 488 mm (19") | 488 mm (19") | 488 mm (19") |
| Exterior dimensions | | | | |
| Width (mm) | 600 | 600 | 600 | 600 |
| Depth (mm) | 800 | 800 | 800 | 800 |
| Height (mm) | 985 | 1385 | 1830 | 2055 |
| Ventilation | 4 fans | 4 fans | 4 fans | 4 fans |
| Wheels | incorporated | incorporated | incorporated | incorporated |
| Front door (optional) | PK-18 | PK-27 | PK-37 | PK-42 |

